Fireplace SIMPLE M/S 8 right BS

SIMPLE/M/S/P/BS

Price:

€629.00

EAN:
5902539505665

Double-sided BS-glazed inserts with split pane. Perfectly fits in the style of modern interiors. This type of fireplace is often chosen for open spaces.



Shipping on pallet
transfer - zł106.00
COD - zł111.00
Implementation within
1 days

Technical Specifications

Rated output (kW)	8,0
Range of heating power (kW)	3.0 - 10.0
Efficiency (%)	80,0
Exhaust outlet diameter (mm)	200
Complies with Ecodesign criteria	Yes
Designed for heat recovery unit	No
Fuel type	recommended seasoned hardwood with moisture ≤20%
Weight (kg)	115,0
CO emission (at 13% O 2) ≤ given in %	0,10
Flue gas temperature (℃)	238,0
Max log length (cm)	330
Emission of dust (mg/Nm^3)	25,0
Compliance with BImSchV 2 standard	Yes
The energy efficiency index EEI	105,40

The minimum active field of exhaust grilles (cm^2)	≥700
The minimum active field of inlet grilles (cm^2)	≥500
Glazing type	lateral
Opening of the doors	to the right
Material	cast iron
Width (cm)	60,00
Height (cm)	70,10
Depth (cm)	36,00
External air inlet	No
The liner of the combustion chamber	No
Ashpan	Yes
Decorative printed glass	No

Features

Double-sided BS-glazed inserts with split pane. Perfectly fits in the style of modern interiors. This type of fireplace is often chosen for open spaces.

MODERN DESIGN

Corner fireplace stove with BS-type doors (combined panes).

The door of the fireplace stove has a modern handle.

MAXIMISING ENERGY EFFICIENCY

Fuel particle burning thanks to the deflector, which extends the exhaust gas path. This process also increases the efficiency of combustion and guarantees better use of energy, thus minimising the emission of harmful substances into the atmosphere.

Spacious combustion chamber, which allows to load a large amount of fuel without the need for frequent adding.

Manual control of the chimney draught by means of a built-in glass pane.

ECOLOGICAL COMBUSTION

The unit meets the requirements of**Ecodesign** standards and the restrictions of the**BImSchV 2** standard, which determines the maximum CO emission.

SAFETY AT THE HIGHEST LEVEL

The front of the cartridge is equipped with heat-resistant ceramics that can withstand temperatures up to 660°C. The glass offered by us has a quality and safety certificate.

Densely placed heat sinks on the external walls of the device guarantee maximum use of heat generated by the cartridge.

The front of the insert is resistant to high temperatures thanks to the use of high quality steel.


COMFORTABLE USE

The device is equipped with a clean glass system - thanks to the so-called curtain, the air stream is distributed evenly, sweeps the glass and minimizes soot build-up. This allows you to keep the glass looking shiny and clean for a long time.

The removable grate and ashtray make it easy to keep the glass cartridge clean.

The decorative hurdle prevents wood from falling out of the firebox.

Technical drawing



Additional options



External air inlet - additional option

€16.36

External air inlet - special connector mounted in fireplace insert, which provides fresh air directly from outside.



Podstawa pod wkład MAJA i ANTEK

€34.11

Podstawa pod wkład MAJA i ANTEK umożliwia stabilne ustawienie wkładu kominkowego, możliwość regulacji wysokości nóżek.



Steel pipe 200/1m

€23.13

Exhaust pipe designed for connecting wood-fired fireplace inserts an the existing flue pipes.



Steel pipe 200/0.5m

€15.89

Exhaust pipe designed for connecting wood-fired fireplace inserts an the existing flue pipes.



Movable elbow 200/90

€22.90

Adjustable elbow up to 90°, 3-segment, diameter: 200 mm.



The passage from the pipe system Ø 200

€27.80

The passage from the pipe system to the ceramic chimney Ø200.

Warranty

All the products available at www.kratki.com are brand new, free from any physical or legal defects. The Producer grants a 5-year warranty from the moment of purchase of an insert for its reliable operation. Grate and sealing for the fireplace are covered with a 1-year warranty from the moment of the purchase of the insert. The warranty shall not cover heat-resistant ceramics. The application of the fireplace insert, the method of joining with the chimney as well as the terms and conditions of use must correspond with the manual.

Return

A Customer being a Consumer, who has concluded the Sales Contract may rescind thereof within a period of 14 days without giving any reasons. The time limits run for the rescission of the Sales Contract shall commence at the time of acquiring the Goods by the Customer or a third party of their choice, other, however, than a carrier. The representations may be submitted in a form whose template has been published by the Seller at the Online Shop Website.